

Process Signal Problem Solvers

Transmit Alarm

Isolate Convert

Split Rescale



Signal Conditioners Are Our Business!

Variable intensity I/O LoopTracker® LEDs*

Output test push button*

Factory ranged or easy-to-set switches

No computer for setup

Free application assistance

Free technical information

We are an application driven company!

Factory service and calibration

Fast delivery

*Most models





APD Series DIN Signal Conditioners and Alarms: api-usa.com/apd





API Series Plug-In Signal Conditioners and Alarms: api-usa.com/api








api-usa.com/8000
api-usa.com/tc
api-usa.com/duopak
api-usa.com/splitter
api-usa.com/dc
api-usa.com/math
api-usa.com/ac
api-usa.com/pot
api-usa.com/freq
api-usa.com/strain
api-usa.com/tc
api-usa.com/rtd
api-usa.com/valve

See datasheets for

Thermocouple Input Dual Output Splitters

APD 41390 Series

- ✓ Split or Convert a T/C to Any Two T/C Types
- ✓ Add Additional Isolated Output to Existing T/C
- ✓ Solve Thermocouple and Instrument Mismatches
- √ 13 T/C Types
- √ 13 T/C Output Types
- ✓ Zero and Span Output Calibration
- ✓ Sink/Source DC Output(s)
- ✓ 8 A Alarm Relay Option



Micro-Based Signal Transmitters

APD Series

- ✓ Field Rangeable Models
- ✓ Universal I/O Models
- ✓ Factory Ranged Models
- √ 13 T/C Types
- √ 15 RTD Types
- √ 7 Thermistor Types
- ✓ DC: mV, V, mA
- ✓ Potentiometers
- ✓ No Computer For Setup
- ✓ Pushbutton Output Calibration
- ✓ Sink/Source Output



CECOMP Digital Pressure and Vacuum Gauges

Performance Under Pressure!

1 Year Warranty

±0.25% or ±0.1% Accuracy

316L SS Sensor

Gauge or Absolute Reference

Vacuum to 5000 PSI

Compound and Bipolar Ranges

Most Engineering Units

Free Application & Technical Assistance

NIST Traceable Certification Available

Factory Service and Calibration

cecomp.com





Applications

Gas Pipeline Pressures

Aircraft Service

Auto Racing

Food Production

Tank Level

Pump Pressures

Leak Down and Hydrostatic Testing

Compressed Air Monitoring

Vacuum Pump Monitoring

Local Display Plus Analog Input to PLC

Battery Powered



Rugged for Portable Use
Auto Racing Tire Pressure
Memory Options
20 Models to Fit Your Needs
Long Battery Life

MADE IN USA



Loop Powered and 4-Wire Transmitters



2-Wire 4-20 mA Xmtr 2-Wire 4-20 mA Xmtr with Power-Off Display Backup 4-Wire 4-20 mA Output 4-Wire 0-2 V Output



Battery Powered Intrinsically Safe



Battery Powered Test Gauge Class I, Div 1, Gr A, B, C, D Gas Pipeline Pressures Aircraft Service





Pressure Alarms



Dual SPDT Relays User Programmable Alarm Status Indicators Optional Analog Output



Low Voltage Powered



Permanent Installations
Operate 24/7 or Use
On/Off Button
8-24 VAC or 9-32 VDC
760 Torr Absolute Model
for Vacuum Systems



ThermoPro® Temperature



100 Ohm RTD
-58.0°F to 392.0°F
-50.0°C to 200.0°C
2.5" to 12" Probe Lengths
Battery Models

Loop Powered Transmitters

Alarm Models



Current Sensors and Switches



AC and DC Transmitters
AC and DC Switches
Models for 5 A to 2000 A
4-20 mA or 0-10 V Output
SSR or Mechanical Relays
Motor Current Monitoring
Battery Monitoring
Electric Heater Current
Lighting System Current
Pump Monitoring
Current Alarms



Absolute Process Instruments Inc. 1220 American Way Libertyville, IL 60048 api-usa.com cecomp.com

